K-BUS KNX V2

KNX Air Quality Sensor V2_V1.3

CSAQI-06/00.1.0x



KNX/EIB

注意事项

1、请远离强磁场、高温、潮湿等环境；

4、请勿自行拆卸本设备。

1

3

4

3.1 4

3.2 4

5

ETS 7

5.1 7

5.2 “General” 7

5.3 “AQI” 10

5.3.1 “AQI General settings” 10

5.3.2 “AQI Value settings” 14

5.3.3 “AQI Alarm settings” 15

5.4 “Temperature” 16

5.5 “Humidity” 20

5.6 “VOC” 23

5.7 “CO2” 25

5.8 “Ventilation controller” 27

5.9 “Logic” 34

37

6.1 AQI 37

6.2 39

6.3 40

6.4 VOC 41

6.5 CO2 42

6.6 43

6.7 44

k KNX

V2 PM2.5/PM10 VOC CO2 AQI

k

PM2.5 ! VOC ! CO2 k KNX

k

KNX V2 KNX 12-30V DC

80 86 k knxprod

ETS (ETS4 k

- **PM2.5 PM10**
-
- **AQI**
- **VOC**
- **CO2**
-
-
-
-

-
- **VOC**
- **CO2**
- **3**
-

CO2 **CO2** **400ppm** **k**

6-8s **CO2**

10s **CO2** **k**

CO2 **CO2** **400ppm** **k**

	21-30V DC
	<3.0mA/24V DC, <2.6mA/30V DC <80mW
	12-30V DC
	<73mA/12V DC, <34mA/24V DC <26mA/30V DC <0.9W
KNX	/
	/
LED	
	-5°C...45°C ±1°C
	0.1°C
	10...90% ±4.5% 0...10% / 90...100% ±8%
	0.1%
	0-999 µg/m³
	50%(ť=0.3um) 98%(ť≥0.5 um) ≤ 10s
VOC	0-9.99 mg/m³ ±10%
CO2	400ppm~2000ppm ®40ppm
	¨ 5 °C... + 45 °C
	– 25 °C ... +55 °C – 25 °C ... +70 °C
	<93%
80 86	
86Ô86Ô48.3mm	
0.15KG	

3.1



3.2



F LED ϟ

F ϶KNX

ϟ

Air Quality Sensor, 6 in 1/2.0	45	120	120

PM2.5 PM10 AQI VOC CO2 k k

AQI CO2 VOC

k

AQI

AQI 6 1bit 4bit 1byte k

AQI

AQI k

/ /

k

k / /

k

1bit 4bit 1byte k

k

VOC

VOC k

CO2

CO2 k

PM2.5 ! VOC ! CO2 3 k 1bit/1byte k

5 AQI 1bit !

AQI 1bit 1bit 1bit VOC 1bit

1bit k 6 k

k

ETS

5.1

k

5.2 “General”

“General settings” 5.2 k



5.2 “General settings”

After voltage recovery or download

“VOC stability time”

VOC k **2mins** k

“CO2 stability time”

CO2 k **2mins** k

"PM2.5/PM10 stability time"

PM2.5/PM10 k **10s** k

"Request external sensor after"

AQI, k

2mins k

"Display PM2.5"

"Display PM10"

"Display AQI level"

"Display temperature"

"Display humidity"

"Display VOC"

"Display CO2"

k

No

Yes

"Yes" "No" k

"Warning buzzer for"

k

Do not used

AQI

Temperature

Humidity

VOC

CO2

“Do not used”

“AQI” “AQI Alarm settings”

“Alarm level” k

“Temperature” “Temperature settings”

“Heating/Frost alarm temperature [0..500]*0.1°C” k

“Humidity” “Humidity settings” “Humidity

alarm value [1..99]%” k

“VOC” VOC “VOC settings” “VOC alarm value

[100..5000]ug/m³” k

“CO2” CO2 “CO2 settings” “CO2 alarm value

[400..2000]ppm” k

k

“Alarm cycle [2..255]”

k **2…255(s)**

“Alarm on proportion [1..100]”

k 2s 50%

1s 1s k **1…100(%)**

5.3 “AQI”

5.3.1 “AQI General settings”

“AQI General settings” 5.3.1 k



5.3.1 “AQI General settings”

“PM2.5/PM10 Real Value”

PM2.5/PM10 KNX k

100%External

10%Internal+90%External

...

100%Internal

“40%Internal+60%External” PM2.5/PM10 A 40%

B 60% = A×40% + B×60% k

“Data type of PM2.5”

“Data type of PM10”

PM2.5 ! PM10 k

Value in ug/m³(DPT_7.001)

"Send AQI level"

k AQI 0

35 ! 36 75 ! 76 115 ! 116 150 ! 151 250 250 k

No send

Send on change

Send cyclically

"No send" AQI k

"Send on change" AQI k

"Send Cyclically" AQI "Send value Cyclically" k

"Send AQI level out value"

AQI k

No send

Send on change

Send cyclically

"No send" "AQI Value settings" k

"Send on change" AQI "AQI Value settings"

k

"Send Cyclically" "AQI Value settings" "Send value Cyclically" k

"Send AQI alarm out value"

AQI k

No send

Send on change

Send cyclically

"No send" "AQI Alarm settings" k

"Send on change" AQI "AQI Alarm settings" "Alarm

Level” k

“Send Cyclically” “AQI Value settings” “Send value Cyclically” k

"Internal measure send on change"

k

5

10

30

50

"Send value Cyclically"

k

10..50000

5.3.2 “AQI Value settings”

“AQI Value settings” AQI k



5.3.2 “AQI Value settings”

“Level x Send Mode”

k

No send

Send 1Bit

...

Send 1bit+4Bit+1Byte

“Level x 1Bit”

1Bit k **0...1**

“Level x 4Bit”

4Bit k **0...15**

“Level x 1Byte”

1Byte k **0...255**

5.3.3 “AQI Alarm settings”

“AQI Alarm settings” 5.3.3 AQI k



5.3.3 “AQI Alarm settings”

“Alarm Level”

AQI “Alarm send mode”

“No alarm send mode” k

Level 2

...

Level 3

“No alarm (Alarm)Send Mode”

k

No send

Send 1Bit

...

Send 1bit+4Bit+1Byte

“No alarm (Alarm) 1 bit”

1Bit k **0...1**

“No alarm (Alarm) 4 bit”

4Bit k **0...15**

"No alarm (Alarm) 1 byte"

1Byte k **0...255**

5.4 "Temperature"

"Temperature settings" 5.4 k



5.4 "Temperature settings"

"Temperature real value"

KNX k

100%External

10%Internal+90%External

...

100%Internal

“40%Internal+60%External” A 40%

B 60% = A×40% + B×60% k

”Internal temperature correction [-100..100]”

k = + k

100%External k **-100...100(*0.1-C)**

”Time period for request external sensor [0...255]min”

k

0..255

”Send temperature value”

k

No send

Send on change

Send cyclically

“No send” k “Send on change”

k “Send cyclically” k

” ” “Send on change”

k

0.1

0.2

...

5


log
1 0(s)
Enable heating/co l a

" " "Cooling/Heating(Stop cooling/heating) 4Bit"

4Bit k **0...15**

" " "Cooling/Heating(Stop cooling/heating) 1Byte"

1Byte k **0...255**

"Heating alarm temperature [0..500]"

k **0...500(*0.1-C)**

"Frost alarm temperature [0..500]"

k **0...500(*0.1-C)**

5.5 “Humidity”

“Humidity settings” 5.5 k



5.5 “Humidity settings”

“Humidity real value”

KNX k

100%External

10%Internal+90%External

...

100%Internal

“40%Internal+60%External” A 40%

B 60% = A×40% + B×60% k

"Internal humidity correction [-30..30]"

k **-30...30(%)**

= + k

100%external k

"Time period for request external sensor [0...255]min"

k

0..255

"Send humidity value"

k

No send

Send on change

Send cyclically

"No send" k "Send on change"

k "Send cyclically" k

"Send on change"

k

0.1

0.2

...

5

"Period of send humidity [10..50000]"

k **10...50000 (*1s)**

"Humidity threshold value 1 [1..99]"

"Humidity threshold value 2 [1..99]"

k **1...99(%)**

0% ~Humidity threshold value 1

Humidity threshold value 1~Humidity threshold value 2

Humidity threshold value 2~ 100% k

Humidity threshold value 1<Humidity threshold value 2

"Humidity hisys time for switchover level [10..50000]"

k **10...50000(s)**

k

"Upper/Middle/Lower send mode"

k

No send

Send 1Bit

...

Send 1bit+4Bit+1Byte

" " "Upper/Middle/ Lower 1Bit"

1Bit k **0...1**

" " "Upper/Middle/Lower 4Bit"

4Bit k **0...15**

" " "Upper/Middle/Lower 1Byte"

1Byte k **0...255**

"Humidity alarm value [1..99]"

k **1...99(%)**

5.6 “VOC”

“VOC settings” 5.6 k



5.6 “VOC settings”

“VOC alarm value [100..5000]”

VOC k mg/m^3, ug/m^3 k

100...5000(ug/m^3)

“Data type of VOC”

VOC k

Value in ug/m3(DPT_7.001)

Float value in ug/m3(DPT_9.030)

“Send VOC value”

VOC k

No send

Send on change

Send cyclically

“No send” VOC k “Send on change” VOC

k “Send cyclically” VOC k

“Send on change”

VOC VOC k

5

10

30

50

“Period of send VOC value [10..50000]”

VOC k **10...50000(s)**

”No alarm(alarm) send mode”

VOC k

No send

Send 1Bit

...

Send 1bit+4Bit+1Byte

“No alarm(Alarm) 1Bit”

VOC 1Bit k **0...1**

“No alarm(Alarm) 4Bit”

VOC 4Bit k **0...15**

“No alarm(Alarm) 1Byte”

VOC 1Byte k **0...255**

5.7 “CO2”

“CO2 settings” 5.7 k



5.7 “CO2 settings”

CO2 alarm value [400..2000]

CO2 k **400...2000(ppm)**

CO2 hysteresis value [100..500]

CO2 k **100...500(ppm)**

700 100 700ppm 600

k

Data type of CO2

CO2 k

Value in ppm(DPT_7.001)

Float value in ppm(DPT_9.008)

Send CO2 value

CO2 k

No send

Send on change

Send cyclically

“No send” CO2 k “Send on change” CO2

k “Send cyclically” CO2 k

Send on change

CO2 CO2 k

5

10

30

50

Period of send CO2 value [10..50000]

CO2 k **10...50000(s)**

No alarm(Alarm) send mode

CO2 k

No send

Send 1Bit

...

Send 1bit+4Bit+1Byte

No alarm(Alarm) 1Bit

CO2 1Bit k **0...1**

No alarm(Alarm) 4Bit

CO2 4Bit k **0...15**

No alarm(Alarm) 1Byte

CO2 1Byte k **0...255**

5.8 “Ventilation controller”



5.8 “Ventilation controller”

“Ventilation controller”

k

Enable

Disable

"Auto.operation on object value"

k

Auto=1/Man.=0

Auto=0/Man.=1

"State of Auto.operation after startup"

k

Enable

Disable

Fan speed output setting

"Data type of fan speed"

k

1bit

1byte

"Object datatype of 1byte fan speed"

1byte k

Fan stage (DPT_5.100)

Percentage (DPT_5.001)

" " "Output value for fan speed low/medium/high"

1byte k

0..255/0..100

" " "Output value for fan speed off/low/medium/high"

1bit k

Low=0,Medium=0,High=0

Low=1,Medium=0,High=0

Low=0,Medium=1,High=0

Low=1,Medium=1,High=0

Low=0,Medium=0,High=1

Low=1,Medium=0,High=1

Low=0,Medium=1,High=1

Low=1,Medium=1,High=1

"Delay between fan speed switch [0..100]*50ms"

1bit k **0..100**

k 0

k

Fan speed control setting

"Control value type"

k

PM2.5

CO2

VOC

"Control value reference from"

k

Local

Bus

"Bus" k

" "Object datatype of PM2.5/VOC"

PM2.5 VOC k PM2.5

VOC k

Value in ug/m3(DPT_7.001)

Float value in ug/m3(DPT_9.030)

DPT_7.001

"Threshold value speed low<-->medium [1..999]/ [1...4000]"

k

k **1..999/1..4000**

"Threshold value speed medium<-->high [1..999]/ [1...4000]"

k

k **1..999/1..4000**

k

OFF <-> <-> <-> k

OFF <-> <-> <-> <->

k

"Hysteresis threshold value in +/- [10...30]/[100..400]"

k

10..30/100..400

CO2 100 450 550 + 350

- 350~550 k

350 550 k



1

2 **k**

2

PM2.5

OFF <-> 20

<-> 40

<-> 70

10

OFF

OFF 30 20+10 k

41 41 40 70

39 39 20 40 k

60 <70-10 k

39 39 20 40

k

3 0

"Minimum time in fan speed [0..65535]s"

k 0..65535

k

k

0 k

k

5.9 “Logic”

5.9 k



5.9(1) “Logic”



5.9(2) “Logic”

"Logic x enable"

k

Enable

Disable

"Input x:"

"Gate function"

k

Do not use

PM value (1bit)

PM alarm value (1bit)

Temperature value (1bit)

Humidity value (1bit)

VOC value (1bit)

CO2 value (1bit)

Extern input value

Logic 1 value

Logic 2 value

"Do not use"

"PM value (1bit)" 6

"PM alarm value (1bit)" 9

"Temperature value (1bit)" 15

"Humidity value (1bit)" 22

"VOC value (1bit)" 26

"CO2 value (1bit)" 26

"Extern input value" 32/36/40

Logic 1 value 34 1 1bit Logic2 ! Logic3

logic 2 ! 3

Logic 2 value 38 2 1bit Logic3 logic 3

KNX/E

k

“C” **“W”**

“R” **“T”** **“U”**

k

6.1 AQI



6.1 AQI

					DPT
1	**PM2.5 value**	**AQI**	**2byte**	**C, R,T**	**7.001 pulses** **9.030 concentration ug/m3**
2	**External PM2.5 value**	**AQI**	**2byte**	**C, W, T, U**	**7.001 pulses** **9.030 concentration ug/m3**
3	**PM10 value**	**AQI**	**2byte**	**C, R,T**	**7.001 pulses** **9.030 concentration ug/m3**
4	**External PM10 value**	**AQI**	**2byte**	**C, W, T, U**	**7.001 pulses** **9.030 concentration ug/m3**
	1 3 PM2.5 PM10 k ug/m^3 2 4 PM2.5 PM10 k ug/m^3				
5	**AQI value**	**AQI**	**2byte**	**C, R,T**	**7.001 pulses**
	0...500 k				
6	**AQI Level**	**AQI**	**1byte**	**C, R,T**	**5.010 counter pulses (0..255)**
	0 35 ! 36 75 ! 76 115 ! 116 150 ! 151 250 250 k				

7	**AQI level out value, 1bit**	**AQI**	**1bit**	**C,T**	**1.001 switch**
8	**AQI level out value, 4bit**	**AQI**	**4bit**	**C,T**	**3.007 dimming control**
9	**AQI level out value, 1byte**	**AQI**	**1byte**	**C,T**	**5.010 counter pulses (0..255)**
“AQI Value settings” k					
10	**AQI alarm out value, 1bit**	**AQI**	**1bit**	**C,T**	**1.001 switch**
11	**AQI alarm out value, 4bit**	**AQI**	**4bit**	**C,T**	**3.007 dimming control**
12	**AQI alarm out value, 1byte**	**AQI**	**1byte**	**C,T**	**5.010 counter pulses (0..255)**
“AQI Alarm settings” k					

6.1 AQI

6.2



6.2

					DPT
13	**Temperature**	**Temperature**	**2 byte**	**C, R,T**	**9.001 temperature (-C)**
k					
14	**External temperature**	**Temperature**	**2 byte**	**C, W, T, U**	**9.001 temperature (-C)**
k					
15	**Heating/Cooling switchover**	**Temperature**	**1bit**	**C, W**	**1.100 heating/cooling**
/ k 1—— 0——					
16	**Heating/Cooling output value, 1bit**	**Temperature**	**1 bit**	**C,T**	**1.001 DPT_Switch**
17	**Heating/Cooling output value, 4bit**	**Temperature**	**4 bit**	**C, T**	**3.007 dimming control**
18	**Heating/Cooling output value, 1byte**	**Temperature**	**1 byte**	**C, T**	**5.010 counter pulses(0..255)**
k					
19	**Heating setpoint**	**Temperature**	**2 byte**	**C, W**	**9.001 temperature (-C)**
k					

20	**Cooling setpoint**	**Temperature**	**2 byte**	**C, W**	**9.001 temperature (-C)**
k					

6.2

6.3

6.3

					DPT
21	**Humidity**	**Humidity**	**2 byte**	**C, R,T**	**9.007 humidity (%)**
k					
22	**External humidity**	**Humidity**	**2 byte**	**C, W, T, U**	**9.007 humidity (%)**
k					
23	**Humidity output value,1bit**	**Humidity**	**1 bit**	**C,T**	**1.001 DPT_Switch**
24	**Humidity output value,4bit**	**Humidity**	**4 bit**	**C, T**	**3.007 dimming control**
25	**Humidity output value,1byte**	**Humidity**	**1 byte**	**C, T**	**5.010 counter pulses (0..255)**
k					

6.3

6.4 VOC

6.4 VOC

					DPT
26	**VOC value**	**VOC**	**2 byte**	**C, R,T**	**7.001 pulses** **9.030 concentration (ug/m3)**
VOC			VOC	k	
27	**VOC value,1bit**	**VOC**	**1 bit**	**C, T**	**1.001 DPT_Switch**
28	**VOC value,4bit**	**VOC**	**4 bit**	**C, T**	**3.007 dimming control**
29	**VOC value,1byte**	**VOC**	**1 byte**	**C, T**	**5.010 counter pulses (0..255)**
VOC			VOC	k	

6.4 VOC

6.5 CO2

6.5 CO2

					DPT
30	**CO2 value**	**CO2**	**2 byte**	**C, R,T**	**7.001 pulses** **9.008 parts/million (ppm)**

CO2

6.6

															Priority
46	Ventilation controller	Fan automatic operation	1 bit	C	-	W	-	U	enable						Low
47	Ventilation controller	PM 2.5 value	2 bytes	C	-	W	T	U	pulses						Low
48	Ventilation controller	Fan speed	1 byte	C	R	-	T	-	fan stage (0..255)						Low
49	Ventilation controller	Fan speed low	1 bit	C	R	-	T	-	switch						Low
50	Ventilation controller	Fan speed medium	1 bit	C	R	-	T	-	switch						Low
51	Ventilation controller	Fan speed high	1 bit	C	R	-	T	-	switch						Low

6.6 Ventilation controller

DPT

46 Fan automatic operation Ventilation controller 1bit C,W,U 1.003 enable

k

1

0

PM 2.5 value 7.001 pulse

47 VOC value Ventilation controller 2byte C,W,T,U 9.030 concentration(ug/m3)

CO2 value 9.008 parts/million(ppm)

“Bus” k PM2.5/VOC/CO2

k ug/m3 ppm k 0~999ug/m3 0~4000ppm

PM2.5 PM2.5 k

48 Fan speed Ventilation controller 1byte C,R,T

5.001 percentage

5.100 fan stage

“1byte” 1byte k

k

49 Fan speed low Ventilation controller 1bit C,R,T 1.001 switch

50 Fan speed medium Ventilation controller 1bit C,R,T 1.001 switch

51 Fan speed hi

6.7



6.7

					DPT
34/38/42	**Logic x output value, 1bit(x=1,2,3)**	**Logic x**	**1 bit**	**C, T**	**1.001 DPT_Switch**
35/39/43	**Logic x output value, 4bit(x=1,2,3)**	**Logic x**	**4 bit**	**C, T**	**3.007 dimming control**
36/40/44	**Logic x output value, 1byte(x=1,2,3)**	**Logic x**	**1 byte**	**C, T**	**5.010 counter pulses (0..255)**
1 0 k					
37/41/45	**Logic x extern input(x=1,2,3)**	**Logic x**	**1 bit**	**C, W**	**1.002 boolean**
k					

6.7